

# Wall mounted unit

## AC fan motor unit for wall mounting

- › High aesthetic cabinet design
- › Optimum air distribution
- › Easy to install
- › Wireless remote control up to 9 m distance
- › 3-speed fan motor
- › Wide operating range
- › Low operating sound level thanks to tangential fan
- › Insulated with self-extinguishing class 1 heat insulation
- › Removable washable air filter (self-extinguishing class 1)



More details and final information can be found by scanning or clicking the QR codes.



Indoor unit			FWT-GT	02	03	04	05	06
			2-pipe					
Cooling capacity (standard conditions)	Total capacity	High	kW	2.40	2.67	3.27	4.49	5.21
		Medium	kW	2.20	2.23	2.79	4.02	4.32
		Low	kW	1.94	2.02	2.52	3.76	4.04
	Sensible capacity	High	kW	1.82	1.99	2.60	3.38	4.03
		Medium	kW	1.73	1.69	2.21	3.00	3.52
		Low	kW	1.50	1.49	1.91	2.77	3.22
Heating capacity (standard conditions)	High	kW	2.71	2.96	3.71	5.07	6.23	
	Medium	kW	2.41	2.62	3.29	4.51	5.38	
	Low	kW	2.06	2.25	2.75	4.03	4.83	
Power input	High	kW	0.031	0.032	0.042	0.053	0.072	
	Medium	kW	0.03		0.04	0.05	0.07	
	Low	kW	0.03		0.04	0.05	0.06	
FCEER			D		C		C	D
FCCOP			C					
Dimensions	Unit	HeightxWidthxLength	mm	288x800x206			310x1,070x224	
Weight	Unit		kg	9.00			14.0	
Casing	Colour	White						
Air filter	Type	Washable Saranet						
Fan	Type	Cross flow fan						
	Quantity	1						
Air flow rate	High	m³/h	442	476	629	866	1,053	
	Medium	m³/h	391	425	544	765	883	
	Low	m³/h	340	374	442	663	782	
Total sound power level	High	dBA	45.0	48.0	55.0		59.0	
	Medium	dBA	41.0	44.0	50.0	51.0	54.0	
	Low	dBA	36.0	39.0	45.0	47.0	51.0	
Sound pressure level	High	dBA	34.0	35.0	42.0		46.0	
	Medium	dBA	29.0	30.0	39.0	38.0	42.0	
	Low	dBA	25.0		32.0	34.0	39.0	
Piping connections	Drain OD	mm	19					
Power supply	Phase/Frequency/Voltage	Hz/V	1N~/50/220-240					
Control systems	Infrared remote control	WRC-HPC						
	Wired remote control	MERCA / SRC-HPA						

For standard conditions refer to the Measuring Conditions table, at the end of this catalogue