


4-way blow ceiling mounted cassette

AC fan motor unit for ceiling mounting.
Possibility to shut 1 or 2 flaps

- > Modern style decoration panel in white (RAL9010)
- > Compact casing (570mm in width and Length) enables unit to fit flush into ceilings and match standard architectural modules, without cutting ceiling tiles
- > Comfortable horizontal auto swing ensures draughtfree operation and prevents ceiling soiling
- > Optional fresh air intake
- > Possibility to shut 1 or 2 flaps for easy installation in corners
- > Standard drain pump with 750mm lift increases flexibility and installation speed



More details and final information can be found by scanning or clicking the QR codes.



FWF-BT



FWF-BF

Indoor unit			FWF-BT/BF		02	03	04	05	2-pipe		4-pipe		02	03	04	05
Cooling capacity (standard conditions)	Total capacity	High kW	1.7	3.0	4.0	4.9	1.8	2.9	3.8	4.6						
		Medium kW	1.5	2.7	3.1	4.0	1.5	2.4	3.1	3.8						
		Low kW	1.3	2.4		2.8	1.3		1.6	2.6						
	Sensible capacity	High kW	1.4	2.0	2.7	3.5	1.5	1.8	2.5	3.2						
		Medium kW	1.2	1.7	2.0	2.7	1.2	1.5	1.9	2.5						
		Low kW	1.0	1.4		1.8			1.0	1.6						
Heating capacity (standard conditions)	High kW	2.4	3.3	4.5	5.6	3.3	3.6	4.7	5.7							
	Medium kW	2.1	2.9	3.5	4.4	2.9	3.1	3.7	4.7							
	Low kW	1.9	2.7		3.0	2.4		2.6	3.2							
Power input	High kW		0.074		0.090	0.118		0.074		0.094	0.121					
	Medium kW		0.067		0.070	0.089	0.067	0.062		0.074	0.093					
	Low kW		0.060		0.055	0.062	0.060	0.055		0.066						
FCEER			22	40	44	45	22	33	34	40						
FCCOP			32	45	49		41	48		49						
Dimensions	Unit	HeightxWidthxLength	mm				285x575x575									
Weight	Unit		kg			19				20						
Fan	Type						Turbo fan									
	Quantity						1									
	Air flow rate	High m³/h	456	468	660	876	468	438	618	822						
		Medium m³/h	384	390	486	648	390	366	456	612						
Total sound power level	Low m³/h	300		318		420	318		300	390						
	High dBA		44.0		50.0	55.0	44.0	46.0	52.0	57.0						
	Medium dBA		40.0		44.0	49.0	40.0	42.0	46.0	51.0						
Sound pressure level	Low dBA	36.0		38.0		42.0	36.0	38.0	41.0	44.0						
	High dBA		31.0		40.0	45.0	31.0	33.0	42.0	47.0						
	Medium dBA		27.0		33.0	39.0	27.0	29.0	35.0	41.0						
Piping connections	Drain OD		mm			26.0		30.0	26.0	27.0						
Power supply	Phase/Frequency/Voltage	Hz/V					VP20 (External dia.26 / Internal dia. 20)									
Control systems	Infrared remote control							BRC7E530 / BRC7E531								
	Wired remote control							BRC315D								

For standard conditions refer to the Measuring Conditions table, at the end of this catalogue