

Concealed ceiling unit with medium ESP

AC fan motor unit for horizontal concealed mounting

- › Compact dimensions, can easily be mounted in a narrow ceiling void
- › Heat exchanger up to 4 rows
- › Drain pan to collect the condensate from: heat exchanger and regulating valves -reversible water connections
- › The air filter can easily be removed for cleaning
- › Available static pressure up to 80Pa at maximum speed



More details and final information can be found by scanning or clicking the QR codes.



FWB-CT

FWB-CF

Indoor unit	FWB-CT/CF	04	05	06	08	10	11	15	17
2-pipe									
Speed		min	med	max	min	med	max	min	med
Declared speed		2,5,7		1,5,7		1,6,7		1,4,7	
Rated air flow (E)	m³/h	109	246	276	171	275	341	195	360
Available static pressure (E)	Pa	10	50	63	19	50	77	19	50
Power input (E)	W	24	57	82	34	69	106	34	85
Maximum current absorption	A	0.40		0.56		0.56		1.10	
Total cooling capacity (1)(E)	kW	0.92	1.72	1.90	1.27	1.90	2.27	1.57	2.69
Sensible cooling capacity (1)(E)	kW	0.61	1.21	1.34	0.89	1.34	1.59	1.07	1.86
FCEER class (E)		D			E			D	
Water flow (1)	l/h	160	306	340	222	339	408	274	476
Water pressure drop (2)(E)	kPa	2	5	6	3	6	8	3	7
Heating capacity (3)(E)	kW	0.88	1.81	1.99	1.33	1.98	2.35	1.59	2.80
FCCOP class (E)		D			C			D	
Water flow (3)	l/h	153	315	346	231	345	408	276	488
Water pressure drop (3)(E)	kPa	1	4	5	2	5	7	2	6
Standard coil - number of rows		3		3		4		3	
Total sound power level (4)	dB(A)	28	49	52	39	50	54	39	50
Inlet + radiated sound power level (4)(E)	dB(A)	26	47	50	37	48	52	37	48
Outlet sound power level (4)(E)	dB(A)	25	46	49	36	47	51	36	47
Water content - standard coil	dm³	1.20		1.20		1.60		1.60	
Power supply cable type		N07V-K							
Cross-section area of power cables (5)	mm²	1.00		1.00		1.00		1.50	
Safety fuse F	A	1		1		1		2	
Fuses type		gG 1~50							
Power supply	Phase/Frequency	Hz	FWEC1A / FWEC2A / FWEC3A / FWCSA / FWTTOUCH / FWEC2T / FWEC4T						
4-pipe									
Speed		min	med	max	min	med	max	min	med
Declared speed		2,5,7		1,5,7		1,6,7		1,4,7	
Rated air flow (E)	m³/h	109	243	270	170	272	336	195	357
Available static pressure (E)	Pa	10	50	63	19	50	77	19	50
Power input (E)	W	24	57	82	34	69	106	34	85
Maximum current absorption	A	0.40		0.56		0.56		1.10	
Total cooling capacity (1)(E)	kW	0.92	1.70	1.86	1.26	1.88	2.24	1.57	2.67
Sensible cooling capacity (1)(E)	kW	0.61	1.20	1.31	0.88	1.33	1.57	1.07	1.84
FCEER class (E)		D			E			D	
Water flow (1)	l/h	160	302	333	221	335	404	274	473
Water pressure drop (2)(E)	kPa	2	5	6	3	6	8	3	7
Heating capacity (3)(E)	kW	1.14	1.93	2.06	1.55	2.07	2.32	2.09	3.09
FCCOP class (E)		C			D			C	
Water flow (3)	l/h	100	169	180	136	181	204	183	271
Water pressure drop (3)(E)	kPa	1	2	3	2	3	3	2	4
Total sound power level	dB(A)	28	49	52	39	50	54	39	50
Additional coil - number of rows (4)		52		39	50	54	39	52	
Inlet + radiated sound power level (4)(E)	dB(A)	26	47	50	37	48	52	37	48
Outlet sound power level (4)(E)	dB(A)	25	46	49	36	47	51	37	48
Water content - standard coil	dm³	0.47			0.59				0.97

(1) Water temperature 7°C / 12°C, air temperature dry bulb 27°C, wet bulb 19°C (47% relative humidity) according to EN1397/2015 | (2) Water temperature 7°C / 12°C, air temperature dry bulb 27°C, wet bulb 19°C (47% relative humidity) | (3) Water temperature 65°C / 55°C, air temperature 20°C | (4) Sound power measured according to standards ISO 3741 and ISO 3742 | (5) Sound pressure measured at a distance of 4 m in a free field with a directivity factor of 1 | (E) EUROVENT certified data