



Auto cleaning filter

for concealed ceiling units

The unique automatic cleaning filter achieves higher efficiency and comfort with lower maintenance costs

Reduce running costs

- › Automatic filter cleaning ensures low maintenance costs because the filter is always clean



Minimal time required for filter cleaning

- › The dust box can be emptied with a vacuum cleaner for fast and easy cleaning
- › No more dirty ceilings

Improved indoor air quality

- › Optimum airflow eliminates draft and insulates sound

Superb reliability

- › Prevents clogged filters for seamless operation

Unique technology

- › Unique and innovative filter technology inspired by the Daikin auto cleaning cassette



How does it work?

- 1 Scheduled automatic filter cleaning
- 2 Dust collects in a dust box that's integrated into the unit
- 3 The dust can easily be removed with a vacuum cleaner

Combination table

	Split / Sky Air				VRV						
	FDXM-F9				FXDA-A/FXDQ-A3						
	25	35	50	60	15	20	25	32	40	50	63
BAE20A62	•	•			•	•	•	•			
BAE20A82									•	•	
BAE20A102			•	•							•



youtube.com/DaikinEurope




Specifications

	BAE20A62	BAE20A82	BAE20A102
Height (mm)	210		
Width (mm)	830	1,030	1,230
Depth (mm)	188		

Concealed ceiling unit with medium ESP

Slimmest yet most powerful medium static pressure unit on the market

- › Ideal solution for small businesses and shops
- › Slimmest unit in class, only 245mm (300mm built-in height) and therefore narrow ceiling voids are no longer a challenge
- › Low operation sound level down to 25dBA
- › Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths
- › Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- › Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- › Multi zoning kit allows multiple individually-controlled climate zones to be served by one indoor unit
- › Reduced energy consumption thanks to specially developed DC fan motor
- › Optional fresh air intake
- › Flexible installation: air suction direction can be altered from rear to bottom suction and choice between free use or connection to optional suction grilles
- › Standard built-in drain pump with 625mm lift increases flexibility and installation speed



with multi zoning option

More details and final information can be found by scanning or clicking the QR codes.



FBA-A(9)



ARXM-R



AZAS-MV1



AZAS-MY1

Efficiency data				FCAG + ARXM / AZAS		71A9 + ARXM71R	100A + AZAS100MV1	125A + AZAS125MV1	140A + AZAS140MV1	100A + AZAS100MY1	125A + AZAS125MY1	140A + AZAS140MY1	
Cooling capacity	Nom.			kW	6.80	9.50	12.1	13.4	9.50	12.1	13.4		
Heating capacity	Nom.			kW	7.50	10.8	13.5	15.5	10.8	13.5	15.5		
Space cooling	Energy efficiency class				A	A	-		A	-			
	Capacity	Pdesign		kW	6.80	9.50	12.1	13.0	9.50	12.1	13.0		
	SEER				5.57	5.25	4.85	5.50	5.25	4.85	5.50		
	ηs,c				-		191	217	-	191	217		
	Annual energy consumption			kWh/a	427	633	1,497	1,418	633	1,497	1,418		
Space heating (Average climate)	Energy efficiency class				A	-		-	A	-			
	Capacity	Pdesign		kW	4.50	6.00		7.80	6.00		7.80		
	SCOP/A				3.81		3.55	3.85	3.81	3.55	3.85		
	ηs,h				-		139	151	-	139	151		
	Annual energy consumption			kWh/a	1,652	2,205	2,366	2,836	2,205	2,366	2,836		
Indoor unit				FBA	71A9	100A	125A	140A	100A	125A	140A		
Dimensions	Unit	HeightxWidthxDepth		mm	245 x1,000 x800							245 x1,400 x800	
Weight	Unit			kg	35.0							46.0	
Air filter	Type				Resin net								
Fan	Air flow rate	Cooling	Low/Medium/High	m³/min	12.5 /15.0 /18.0	23.0 /26.0 /29.0	23.5 /29.0 /34.0		23.0 /26.0 /29.0		23.5 /29.0 /34.0		
		Heating	Low/Medium/High	m³/min	12.5 /15.0 /18.0	23.0 /26.0 /29.0	23.5 /29.0 /34.0		23.0 /26.0 /29.0		23.5 /29.0 /34.0		
	External static pressure		Nom./High	Pa	30 /150	40 /150	50 /150		40 /150		50 /150		
Sound power level	Cooling			dBA	56.0	58.0	62.0		58.0		62.0		
Sound pressure level	Cooling	Low/Medium/High		dBA	25.0 /28.0 /30.0	30.0 /32.0 /34.0	32.0 /35.0 /37.0		30.0 /32.0 /34.0		32.0 /35.0 /37.0		
	Heating	Low/Medium/High		dBA	25.0 /28.0 /31.0	30.0 /33.0 /36.0	32.0 /35.0 /38.0		30.0 /33.0 /36.0		32.0 /35.0 /38.0		
Control systems	Infrared remote control				BRC4C65 / BRC4C66								
	Wired remote control				BRC1H52W/S/K / BRC1E53A / BRC1E53B / BRC1E53C / BRC1D52								
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220								
Outdoor unit				ARXM71R	AZAS100MV1	AZAS125MV1	AZAS140MV1	AZAS100MY1	AZAS125MY1	AZAS140MY1			
Dimensions	Unit	HeightxWidthxDepth		mm	734 x954 x401		990 x940 x320						
Weight	Unit			kg	49.0	70		78	70		77		
Sound power level	Cooling				-	70	71	73	70	71	73		
					-	-	71	73	-	71	73		
Sound pressure level	Cooling	Nom.		dBA	52.0	53		54	53		54		
	Heating	Nom.		dBA	52.0	57							
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		-5 ~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~18		-15 ~15.5						
Refrigerant	Type/GWP				R-32/675								
	Charge			kg/TCO2Eq	1.15 /0.780		2.60 /1.76		2.90 /1.96		2.60 /1.76	2.90 /1.96	
Piping connections	Liquid/Gas OD			mm	9.52 /15.9								
	Piping length	OU - IU	Max.	m	30								
		System	Equivalent	m	-	50							
			Chargeless	m	-	30							
	Additional refrigerant charge			kg/m	0.035 (for piping length exceeding 1m)	See installation manual							
	Level difference IU - OU		Max.	m	20.0		30.0						
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240								
Current - 50Hz	Maximum fuse amps (MFA)			A	-	25	32		16				

Contains fluorinated greenhouse gases