

Concealed floor standing unit

Designed to be concealed in walls

- › Combination with Sky Air Alpha-series ensures best in class quality, highest efficiency and performance
- › Discretely concealed in the wall: only the suction and discharge grilles are visible
- › Requires very little installation space as the depth is only 200 mm
- › Its low height (620 mm) enables the unit to fit perfectly beneath a window
- › High ESP allows flexible installation



More details and final information can be found by scanning or clicking the QR codes.



FNA-A9



RZAG-A

Efficiency data		FNA + RZAG		35A9 + 35A		50A9 + 50A		60A9 + 60A			
Cooling capacity	Min./Nom./Max.	kW		1.6/3.5/4.5		1.7/5.0/6.0		1.7/6.0/6.5			
Heating capacity	Min./Nom./Max.	kW		1.40/4.00/5.00		1.70/5.00/6.00		1.70/7.00/7.50			
Space cooling	Energy efficiency class					A+					
	Capacity	Pdesign	kW	3.50		5.00		6.00			
	SEER					5.90		5.70			
	Annual energy consumption			kWh/a		208		297			
Space heating (Average climate)	Energy efficiency class					A					
	Capacity	Pdesign	kW	3.50		4.30		4.50			
	SCOP/A					3.90					
	Annual energy consumption			kWh/a		1,255		1,542			
Indoor unit		FNA		35A9		50A9		60A9			
Dimensions	Unit	HeightxWidthxDpeth		mm		620/720x1,190x200		620/720x1,190x200			
Weight	Unit			kg		23.0		30.0			
Air filter	Type						Resin net				
Fan	Air flow rate	Cooling	Low/High	m ³ /min	7.3/8.7		13.5/16.0				
		Heating	Low/High	m ³ /min	7.3/8.7		13.5/16.0				
	External static pressure		Nom./High	Pa	30/48		40/49				
Sound power level	Cooling			dB(A)	53.0		56.0				
Sound pressure level	Cooling	Low/Medium/High		dB(A)	28.0/31.0/33.0		30.0/33.0/36.0				
	Heating	Low/Nom./High		dB(A)	28.0/31.0/33.0		30.0/33.0/36.0				
Control systems	Infrared remote control					BRC4C65					
	Wired remote control					BRC1H52W/S/K / BRC1E53A / BRC1E53B / BRC1E53C / BRC1D52					
Power supply	Phase/Frequency/Voltage		Hz/V			1~/50/60/220-240/220					
Outdoor unit		RZAG		35A		50A		60A			
Dimensions	Unit	HeightxWidthxDpeth		mm		734x870x373					
Weight	Unit			kg		52					
Sound power level	Cooling			dB(A)	62.0		63.0		64.0		
	Heating			dB(A)	62.0		63.0		64.0		
Sound pressure level	Cooling	Nom.		dB(A)	48.0		49.0		50.0		
	Heating	Nom.		dB(A)	48.0		49.0		50.0		
Operation range	Cooling	Ambient	Min.~Max.	°CDB			-20~-52				
	Heating	Ambient	Min.~Max.	°CWB			-20~-24				
Refrigerant	Type/GWP					R-32/675.0					
	Charge			kg/TCO ₂ Eq			1.55/1.05				
Piping connections	Liquid/Gas OD		mm		6.35/9.50		6.35/12.7				
	Piping length	OU - IU	Max.	m			50				
	Additional refrigerant charge		System Chargeless		m			30			
	Level difference IU - OU		Max.		kg/m			0.02 (for piping length exceeding 30m)			
	Power supply		Phase/Frequency/Voltage		Hz/V			1~/50 / 220-240			

Contains fluorinated greenhouse gases